



PORTABLE WINCH - Accessori

Carrucole



PCA-1270

PCA - 1270

Carrucola singola



The corner block lets you change the line pull direction of a log to avoid obstacles or to position it parallel to the trail. The corner block is therefore very useful with an ATV (QUAD) or our Portable WinchTM to get some lift on the rope or to double your line (and power). Use it with the pulley facing down for best results since it will prevent the rope from jumping out of the block when there is a slack and will jump easier of it when used in combination with the automatic release (PCA-1291).

CARATTERISTICHE	
Applicazioni	forestale, caccia, off road
Peso	2,4 kg
Diametro	100 mm
Lunghezza	25 cm
Larghezza	10 cm
Diametro max fune	13 mm
Diametro min fune	6 mm
Materiale	acciaio zincato

PCA-1271

PCA-1271



Carrucola autobloccante in alluminio con flange rotanti

The self-locking pulley is especially designed for rescue operations. It features a brake cam system which allows the rope to go through freely in one direction and blocks it in the other direction. The spring-loaded cam can be disengaged by pulling a release cord. The 62 mm (2-1/2") diameter aluminum pulley is mounted on self-lubricating bushing and stainless steel axle. The swing sides are also made of anodized aluminum.

CARATTERISTICHE	
Applicazioni	Cavo, filo, installazione in fibra ottica, cantiere, agricoltura, forestale, apparecchi di sollevamento, caccia, applicazioni marine, Off road, ricerca e salvataggio, tenda, lavori in altezza
Peso	655 g
Diametro	62 mm
Lunghezza	22,5 cm
Larghezza	8,5 cm
Altezza	4,5 cm
massima resistenza alla rottura	4000 kg
Diametro max fune	13 mm
Diametro min fune	10 mm
Materiale	alluminio anodizzato
Garanzia	1 anno

PCA-1272

PCA-1272

Carrucola autobloccante doppia in alluminio con flange rotanti



The self-locking pulley is especially designed for rescue operations. It features a brake cam system that allows the rope to go through freely in one direction and blocks it in the other direction. The spring-loaded cam can be disengaged by pulling a release cord. When used in a system (with a matching double pulley), it provides 4:1 mechanical advantage. Both 62 mm (2-1/2") diameter aluminum pulleys are mounted on self-lubricating bushings and stainless steel axles. The swing sides and the main plate are also made of anodized aluminum.

CARATTERISTICHE	
Applicazioni	Cavo, filo, installazione in fibra ottica, cantiere, agricoltura, forestale, apparecchi di sollevamento, caccia, applicazioni marine, Off road, ricerca e salvataggio, tenda, lavori in altezza
Peso	920 g
Diametro	62 mm
Lunghezza	22,5 cm
Larghezza	8,5 cm
Altezza	7 cm
massima resistenza alla rottura	4000 kg
Diametro max fune	13 mm
Diametro min fune	10 mm
Materiale	alluminio anodizzato
Garanzia	1 anno

PCA-1273

PCA-1273

Carrucola doppia con flange rotanti in acciaio inox



For extra heavy loads, you can multiply the winches' power using pulleys. This double pulley features the same aluminum and stainless steel construction as our stainless steel swing side snatch block (PCA-1274) but with two 100 mm (4") diameter deep groove aluminum sheaves. Using one double pulley (positioned at the load) with a single pulley, you can triple the pulling power of the winches. With two double pulleys, an amazing 4 tons of force can be exerted on a load (using the PCW5000)!

CARATTERISTICHE	
Applicazioni	Cavo, filo, installazione in fibra ottica, cantiere, agricoltura, forestale, apparecchi di sollevamento, caccia, applicazioni marine, Off road, ricerca e salvataggio, tenda, lavori in

	altezza
Peso	1,9 kg
Diametro	100 mm
Lunghezza	23 cm
Larghezza	11 cm
Altezza	8,5 cm
massima resistenza alla rottura	4400 kg
Diametro max fune	13 mm
Diametro min fune	6 mm
Materiale	Alluminio e acciaio inox
Garanzia	1 anno

PCA-1274

PCA-1274

Carrucola singola con flangerotanti in acciaio inox



The swing-side snatch block features a lightweight 100 mm (4") diameter deep groove aluminum sheave, with stainless steel plates that swing open to install rope. Sintered bronze bushing on stainless steel shaft provides 98% efficiency. Particularly useful for use when doubling the line, the rope cannot accidentally come out of the block. Use the steel locking carabiners or shackles to anchor to a polyester sling.

CARATTERISTICHE	
Applicazioni	Cavo, filo, installazione in fibra ottica, cantiere, agricoltura, forestale, apparecchi di sollevamento, caccia, applicazioni marine, Off road, ricerca e salvataggio, tenda, lavori in altezza
Peso	1,1 g
Diametro	100 mm
Lunghezza	22 cm
Larghezza	11 cm
Altezza	5,5 cm
massima resistenza alla rottura	2200 kg
Diametro max fune	13 mm
Diametro min fune	6 mm
Materiale	Alluminio e acciaio inox
Garanzia	1 anno

PCA-1275

PCA - 1275



Carrucola singola

Smaller and lighter than the PCA-1274 pulley, this swing-side snatch block features a lightweight diameter deep groove aluminum sheave, with stainless steel plates that swing open to install rope. Useful to deviate the load or to double the line. Ideal to use with the PCW3000.

CARATTERISTICHE	
Applicazioni	Cavo, filo, installazione in fibra ottica, cantiere, agricoltura, forestale, apparecchi di sollevamento, caccia, applicazioni marine, Off road, ricerca e salvataggio, tenda, lavori in altezza
Peso	560 g
Diametro	76 mm
Lunghezza	15 cm
Larghezza	8 cm
Altezza	3 cm
massima resistenza alla rottura	1600 kg
Diametro max fune	10 mm
Diametro min fune	6 mm
Materiale	acciaio inossidabile
Garanzia	1 anno

Fotogalleria

