

GENERATING SET GE 7554 HBS

- ☐ HONDA OHV petrol engine
- ☐ Engine shut down for low level oil
- ☐ Three phase synchronous alternator IP54
- ☐ Output sockets : 1 x 400V 16A 3P+N+T CEE
2 x 230V 16A 2P+T SCHUKO
- ☐ Isometer
- ☐ Circuit breaker
- ☐ Frame
- ☐ Manual trolley (n. 4 foldable handles) TRM-7554 (option)
- ☐ Manual trolley CTM200 (option)
- ☐ Meets EC directives for safety and noise level



Standard equipment 											
Options on request 	• 400 V plug • 230V plug				• Earthing kit				• Manual trolley CTM200 • Manual trolley TRM-7554 (n. 4 foldable handles)		

Technical Data

GE 7554 HBS

A.C. GENERATION - 50 Hz

Three-phase synchronous alternator, self-excited, self-regulated, brushless

* Stand-by three-phase power

7.5 kVA (6 kW) / 400V / 10.8A

* PRP three-phase power

6.5 kVA (5,2 kW) / 400V / 9.4A

* PRP single-phase power

5 kVA / 230V / 21.7A

Cos φ

0.8

Insulation class

H

* Output powers according to ISO 8528-1

ENGINE

4-stroke petrol, OHV, air cooled

Model

HONDA GX 390

* Stand-By net power

7.7 kW (10.5 HP)

* PRP net power

6 kW (8.1 HP)

Cylinders/ Displacement

1 / 389 cm³

Speed

3000 rpm

Fuel consumption (75% of PRP)

2.5 l/h

* Maximum output according to ISO 3046-1

GENERAL SPECIFICATIONS

Tank capacity

6.1 l

Running time (75% of PRP)

2.5 h

IP protection degree

IP 54

*Dimensions LxWxh (mm)

910 x 525 x 613 mm

*Dry weight

105 kg

**Measured acoustic power LwA (pressure LpA)

96 dB(A) (71 dB(A) @ 7m)

**Guaranteed acoustic power LwA (pressure LpA)

97 dB(A) (72 dB(A) @ 7m)

* Dimensions and weight without trolley/trailer.

** Acoustic power according to European Directive 2000/14/EC

Mosa reserves the right to change this specification without notice. For further information please contact the sales department.